

HIGHLY MOISTURE RESISTANT

FSC°-CERTIFIED PARTICLEBOARD

NAF-NO ADDED FORMALDEHYDE

100% POST-INDUSTRIAL RECYCLED/RECOVERED CONTENT

DECLARE PRODUCT

HIGH PINE CONTENT

CARB EXEMPT

EPA TSCA TITLE VI COMPLIANT



CollinsWood.com





MR50 panel is FSC®-certified, NAF, CARB Exempt, contains 100% postindustrial/pre-consumer recycled & recovered fibers, and is the first MR50 rated particleboard on the market.



Highly moisture-resistant

- FSC°-certified particleboard ■ NAF - no added formaldehyde
- High percentage of Western Pine fiber
- Excellent machinability—extends tool life
- Consistent light tan color—best for thin papers and melamines
- No thin edges—panels sawn after sanding
- EPA TSCA Title VI Compliant
- Declare Product
- 100% post-industrial recycled/recovered content

Physical Properties

Density	49 lbs/cu ft	
Internal Bond	150 psi	
Modulus of Rupture	2,500 psi	
Modulus of Elasticity	410,000 psi	
Screw Holding - Face	300 lbs	
Screw Holding - Edge	240 lbs	

Sizes/Thickness

Press Size	5' x 24'
Thickness	5/8" to 1-1/8"
Thickness Tolerance	$\pm.003"$ average thickness from target
L/W Tolerance	± 1/16"
Squareness Tolerance	± 1/32" per foot of panel width

Physical properties tested using method ASTM D 1037-06a. Complies and meets the moisture resistance characteristics defined by ANSI A208.1-2022.

Collins Pine FreeForm® MR50 Particleboard passes the stringent MR50 criteria for both thickness swell and advanced aging / degradation. Our NAF resin enables our products to be third-party certified CARB Exempt TSCA Title VI.

INFORMATION & SALES

Steve Stoler

sstoler@collinsco.com 503.826.5222

Dominic Mattos Jr.

dmattos@collinsco.com 503.826.5226

Toll Free: 800.547.1793

Manufactured at: 6410 Highway 66 Klamath Falls, OR 97601

COLLINSWOOD® FSC

Made in Klamath Falls, Oregon USA

SCS Validation SCS-NAF-04354

- Hardwood Lumber
- Softwood Lumber
- Collins Pine Particleboard
- Collins Pine FreeForm® Particleboard
- TruWood® Siding | Trim
- Collins Pine UniForm[™]



